




## BAG INSERTER ZIM-31

From a roll of polyethylene film, the compact ZIM-31 automatically inserts bags into boxes, crates or trays.

The bag inserter runs with **made-to-measure bags** or **pre-made bags from a 12 kg reel** and handles multi box footprints.



made-to-measure  
bags from a reel



pre-made bags  
from a reel

SOF  
seal off first



### Case lining convenience

- Continuous production thanks to the **automatic film roll exchange**.
- Super **compact**: only 1,7 x 1,3 m floor space needed.
- **15" HMI** to facilitate operator convenience.

### Your intelligent bag inserter

- **Up to 12 cases/minute**.
- Quick and **ergonomic film roll loading**.
- **Patented smart film opening technology**.



Watch our videos  
at [pattyn.com](https://pattyn.com)

# TECHNICAL SPECIFICATIONS ZIM-31

## Made-to-measure bags from a reel

- Continuous tubular gusseted film on a reel.
- Impulse sealing for a controlled and clean seal.

## Pre-made bags from a reel

- Pre-sealed and perforated bags on a reel for optimal convenience.

## Failsafe bag opening

- New strong gripper and spoon module.
- Patented smart film opening technology with a special vacuum and air insertion system.

## Perfectly controlled bag insertion

- Case flap holders for perfect case flap positioning.
- Servo driven up and down movement of the gripper frame for a steady and smooth operation.

## Operator friendly design


- Good maintenance accessibility.
- Improved interface with 15" HMI to facilitate operator convenience.

## Standard equipped with:

- 15" HMI.
- Multicolour warning light.
- Infeed conveyor with integrated box centering device and separator.



Mechanical grippers & spoons



Case flap holders




Automatic film roll exchange (optional)



15 " HMI

## CONTAINER SPECIFICATIONS (For other dimensions, please contact Pattyn)

Type	Boxes, trays and crates
Range [L x W // D] mm	<b>Multi footprint (L x W) /variable heights</b> Min. 300 (L) x 200 (W) // 250 (D) Max. 610 (L) x 410 (W) // 650 (D)
	Outside dimensions

## FILM SPECIFICATIONS


Type	Tubular film with gussets
Thickness	As from 15 µm
Weight of film roll	Max. 12 kg
Outside diameter film roll	Max. 230 mm
Inside diameter of core	76 mm

## OUTPUT AND CONSUMPTION

Output	Up to 12 c/min <i>(Depending on case sizes)</i>
Installed power	4,5 kW
Voltage	3 x 400 V + N + E / 50 Hz
Air supply	6 bar / 1/2" min
Air consumption	45 NI / cycle
Weight	650 kg

## OPTIONS (More options are available, please contact Pattyn)

Automatic film roll exchange	Advanced stainless steel execution
Access point for remote support	Air plunger for improved bag positioning
Automatic format change	



Machine height with film roll door closed: 2095 mm  
Machine height with film roll door open: 2255 mm

Pattyn Packing Lines nv  
Industriepark 'Blauwe Toren'  
Hoge Hul 2, 8000 Brugge - Belgium

T +32 (0) 50 450 480  
info@pattyn.com  
www.pattyn.com



The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customised executions please contact Pattyn. ZIM-31 2019 - V01

**PATTYN®**

Turnkey solutions for industrial packaging.